

TRUPON[®] HP OIL

hydrophobing pull-up oil

| | |
|----------------|---------------------------------------|
| Basis: | synthetic hydrophobing fatty material |
| Appearance: | pale coloured oil |
| Active matter: | approx. 100 % |

Properties:

TRUPON HP OIL can be used alone or in combination with **TRUPON HP WAX**, depending upon the effect required.

When used alone **TRUPON HP OIL** will produce oily pull-up effects.

TRUPON HP OIL can be applied by roller coater, curtain coater or spraying.

Leathers which have been processed utilising waterproofing materials such as **TRUPOSIST[®] WRM** or the **TRUPOSIST** system will exhibit enhanced water resistance and lower water uptake when treated with **TRUPON HP OIL**. Extended drying or conditioning of the leather is not required due to the absence of solvents in the system.

Application:

TRUPON HP OIL when used in admixture with **TRUPON HP WAX** will have the effect of reducing the melting point of **TRUPON HP WAX** and as such allowing interesting effects to be obtained.

When using **TRUPON HP OIL** together with **TRUPON HP WAX** pretrials should be made to establish the mixing ratio required.

TRUPON HP OIL when used in admixture with **TRUPON HP WAX** should be added to the premelted **TRUPON HP WAX** in the amount required in order to obtain a clear, homogeneous liquid.

Safety and storage:

When handling **TRUPON HP OIL**, normal safety precautions associated with the handling of chemicals should be observed. For more specific details please refer to our safety data sheets.

TRUPON HP OIL can be stored for up to 18 months, if temperatures below 5 °C and above 40 °C can be avoided. On prolonged storage or extremes of temperature **TRUPON HP OIL** may exhibit some settlement which can be rectified by either warming and/or stirring the product thoroughly before use.