

# TRUPOTAN<sup>®</sup> AMP

## polymer retanning agent

Basis:	synthetic polymers
Appearance:	brown, viscous liquid
Charge:	anionic
Active matter:	approx. 47 %
pH value(1 : 10):	approx. 7
Light fastness:	excellent
Heat yellowing:	excellent

### **Properties:**

**TRUPOTAN AMP** is a fluid retanning agent based upon synthetic polymers, ideal for producing all types of leather.

**TRUPOTAN AMP** produces leather with very good softness and fullness, with a fine tight grain.

**TRUPOTAN AMP** levels the dyeings without bleaching.

### **Application:**

**TRUPOTAN AMP** is normally applied in a fresh float after the neutralisation, but can also be applied during the neutralisation process.

The application pH should lie over pH 4. The quantity applied is normally between 4 and 10 %, based on shaved weight and is dependent on the required filling effect.

### **Safety and storage:**

When handling **TRUPOTAN AMP**, normal safety precautions associated with the handling of chemicals should be observed. For more specific details please refer to our safety data sheets.

**TRUPOTAN AMP** can be stored for up to 12 months, if temperatures below 5 °C and above 40 °C can be avoided. On prolonged storage or extremes of temperature **TRUPOTAN AMP** may exhibit some settlement which can be rectified by either warming and/or stirring the product thoroughly before use.