

PASTOSOL® U

degreasing and emulsifying agent

Appearance:	colourless liquid
Charge:	non-inonic / anionic
Active matter:	approx. 38 %
pH value (1 : 10):	approx. 7

Properties:

PASTOSOL U is a biodegradable degreasing, dispersing and emulsifying agent.

PASTOSOL U improves the cleanliness and contributes to brilliant wet blue colour.

PASTOSOL U is preferably used for raw material with a high fat content.

PASTOSOL U is free from alkylphenol.

PASTOSOL U does not inhibit the activity of enzymatic products.

Application:

PASTOSOL U can be used in all process steps for production of wet blue.

The degreasing effect is improved if applied together with enzymatic products, such as **TRUPOWET**[®] in the soak and **TRUPOZYM**[®] in the bate.

The necessary quantity of **PASTOSOL U** depends on raw material and process step. The usual dosage for cattle hides is 0.2 - 0.7 %.

PASTOSOL U can be also used in the degreasing of pickled sheep skins. Quantities to be used will vary, depending upon the type and origin of the skins and their natural grease content. Up to 5% in the de-pickling float followed by additions of 0.3-0.8% in the subsequent washing process will normally afford good results.

1/2

11/2016

The information given in this technical leaflet is offered in good faith and is based upon our knowledge and experience of the products used. The suitability of the products mentioned to obtain specific properties or effects are given without obligation or guarantee and should be fully tested by the end user and adapted to suit prevailing works conditions or other products which may be employed.

Safety and storage:

When handling **PASTOSOL U**, normal safety precautions associated with the handling of chemicals should be observed. For more specific details please refer to our safety data sheets.

PASTOSOL U can be stored for up to 24 months, if temperatures below 5 °C and above 40 °C can be avoided.

2/2

11/2016

The information given in this technical leaflet is offered in good faith and is based upon our knowledge and experience of the products used. The suitability of the products mentioned to obtain specific properties or effects are given without obligation or guarantee and should be fully tested by the end user and adapted to suit prevailing works conditions or other products which may be employed.