

TRUPOTAN® NCR

polymer retanning agent

Basis:	modified acrylic polymer
Appearance:	viscous liquid
Charge:	anionic
Active matter:	approx. 30 %
pH value(1 : 10):	approx. 4
Light fastness:	excellent
Heat yellowing:	excellent

Properties:

TRUPOTAN NCR is a polymer retanning agent, based on modified acrylic polymers intended for the tanning and retanning of all types of leather.

TRUPOTAN NCR improves the fullness and grain tightness producing especially fine grained leather.

TRUPOTAN NCR encourages a good chrome fixation and distribution in the final leather.

TRUPOTAN NCR improves the penetration of the dyestuff with minimal loss of dye intensity.

Application:

In chrome tanning between 0.5 and 1.0 % **TRUPOTAN NCR** can be applied to improve the grain tightness of the wet blue. The pH-value of the chrome tanning should lie over pH 3 before application of the **TRUPOTAN NCR**.

In the rechrome between 1.5 to 3.0 % **TRUPOTAN NCR** may be applied, based on shaved weight, to improve the fullness and grain tightness.

1/2

08/2013

The information given in this technical leaflet is offered in good faith and is based upon our knowledge and experience of the products used. The suitability of the products mentioned to obtain specific properties or effects are given without obligation or guarantee and should be fully tested by the end user and adapted to suit prevailing works conditions or other products which may be employed.

Safety and storage:

When handling **TRUPOTAN NCR**, normal safety precautions associated with the handling of chemicals should be observed. For more specific details please refer to our safety data sheets.

TRUPOTAN NCR can be stored for up to 24 months, if temperatures below 5 °C and above 40 °C can be avoided. On prolonged storage or extremes of temperature **TRUPOTAN NCR** may exhibit some settlement which can be rectified by either warming and/or stirring the product thoroughly before use.

2/2

08/2013

The information given in this technical leaflet is offered in good faith and is based upon our knowledge and experience of the products used. The suitability of the products mentioned to obtain specific properties or effects are given without obligation or guarantee and should be fully tested by the end user and adapted to suit prevailing works conditions or other products which may be employed.