

# OELBASE 770

REACH registration number 01-2119491309-30-0000

Basis:	100 % blown rape-seed oil
Appearance:	yellow to brown, viscous liquid
Kinematic viscosity (at 25°C):	approx. 2100 mm <sup>2</sup> /s
Kinematic viscosity (at 40°C):	approx. 770 mm <sup>2</sup> /s
Kinematic viscosity (at 50°C):	approx. 440 mm <sup>2</sup> /s
Activity:	100 % blown rape-seed oil

## **Properties:**

**OELBASE 770** is made of rape-seed oil. **OELBASE 770** has a defined viscosity and is water-insoluble.

## **Application:**

**OELBASE 770** is a raw material utilised in the lubricant sector.

**OELBASE 770** is used as lubricant in emulsifiable and non emulsifiable liquids for treating metals.

**OELBASE 770** is also used as a base for chainsaw oils.

## **Storage:**

**OELBASE 460** should be kept in a dry place at temperatures between 5°C and 40°C.

## **Packaging:**

**OELBASE 770** is available in drums (200 kg), in IBCs (950 kg, extra wide 3'' outlet) and tank truck delivery.

**Safety information:**

Please observe general safety regulations for chemicals when handling **OELBASE 770**.

Please pay also attention to the information given in our safety data sheet.