

# TRUPOTAN® QL

## auxiliary syntan

Basis:	naphthalene compounds
Appearance:	dark brown liquid
Charge:	anionic
Active matter:	approx. 50 %
pH value(1 : 10):	approx. 3.5
Light fastness:	excellent
Heat yellowing:	good

#### **Properties:**

**TRUPOTAN QL** is a pre- and retanning syntan intended mainly for vegetable tanned leather, based on naphthalene.

**TRUPOTAN QL** eases the penetration of the vegetable tannins in the tanning and retanning processes.

### **Application:**

In the pretanning between 5 and 8 % TRUPOTAN QL is applied, calculated on pelt weight.

In the retanning between 2 and 6 % **TRUPOTAN QL** is applied, based on shaved weight. In the retannage the **TRUPOTAN QL** will accelerate the penetration of anionic dyes, syntans and polymers.

During the retannage of sheep, goat and calf skins between 2 and 6 % **TRUPOTAN QL** together with the chrome in the rechrome will improve the fineness and tightness of the grain.

1/2

03/2016

The information given in this technical leaflet is offered in good faith and is based upon our knowledge and experience of the products used. The suitability of the products mentioned to obtain specific properties or effects are given without obligation or guarantee and should be fully tested by the end user and adapted to suit prevailing works conditions or other products which may be employed.

#### **Safety and storage:**

When handling **TRUPOTAN QL**, normal safety precautions associated with the handling of chemicals should be observed. For more specific details please refer to our safety data sheets.

**TRUPOTAN QL** can be stored for up to 18 months, if temperatures below 5 °C and above 40 °C can be avoided. On prolonged storage or extremes of temperature **TRUPOTAN QL** may exhibit some settlement which can be rectified by either warming and/or stirring the product thoroughly before use.

2/2

03/2016

The information given in this technical leaflet is offered in good faith and is based upon our knowledge and experience of the products used. The suitability of the products mentioned to obtain specific properties or effects are given without obligation or guarantee and should be fully tested by the end user and adapted to suit prevailing works conditions or other products which may be employed.