

TRUPOSYL® LL purely synthetic fatliquor

Basis:	polymers and synthetic raw materials
Appearance:	yellow liquid
Charge:	anionic
Active matter:	approx. 45 %
pH value(1 : 10):	approx. 7.5
Acid stability:	medium
Salt stability:	excellent
Chrome stability:	excellent
Light fastness:	excellent
Heat yellowing:	excellent

Properties:

TRUPOSYL LL is a purely synthetic fatliquor for the production of all soft leather types.

Due to its purely synthetic base **TRUPOSYL LL** can be used to produce light, fluffy leathers.

TRUPOSYL LL meets the stringent demands laid down for automotive leathers.

TRUPOSYL LL, in combination with other fatliquors, improves greatly their penetration and uptake.

TRUPOSYL LL can be used for wet-blue as well as for wet-white.

Application:

TRUPOSYL LL can be used alone or in combination with other anionic fatliquors.

1/2

04/2016

The information given in this technical leaflet is offered in good faith and is based upon our knowledge and experience of the products used. The suitability of the products mentioned to obtain specific properties or effects are given without obligation or guarantee and should be fully tested by the end user and adapted to suit prevailing works conditions or other products which may be employed.

Quantities to be used will depend upon the degree of softness required, but will normally vary between 8 – 12 %, based on shaved weight .

Safety and storage:

When handling **TRUPOSYL LL**, normal safety precautions associated with the handling of chemicals should be observed. For more specific details please refer to our safety data sheets.

TRUPOSYL LL can be stored for up to 18 months, if temperatures below 5 °C and above 40 °C can be avoided.

On prolonged storage or extremes of temperature **TRUPOSYL LL** may exhibit some settlement which can be rectified by either warming and/or stirring the product thoroughly before use.

2/2

04/2016

The information given in this technical leaflet is offered in good faith and is based upon our knowledge and experience of the products used. The suitability of the products mentioned to obtain specific properties or effects are given without obligation or guarantee and should be fully tested by the end user and adapted to suit prevailing works conditions or other products which may be employed.